MATERIAL SAFETY DATA SHEET





SUMA DIP K1 Liquid Presoak

HMIS	HMIS NFPA			Personal protective equipment	
Health	3		-	NIL CONTRACTOR	
Flammability	0				
Physical Hazard / Instability	0				
•	-	•			

Version Number: 1 Preparation date: 2014-04-16

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: SUMA DIP K1 Liquid Presoak

SDS #: MS0300400 **Product Code**: 3331251

Recommended use: • Warewashing product

• This product is intended to be diluted prior to use

Manufacturer, importer, supplier:Canadian HeadquartersUS HeadquartersSealed Air - CanadaSealed Air3755 Laird Road

8215 Forest Point Blvd. Mississauga, Ontario L5L 0B3 Charlotte, NC 28273-5509 Phone: 1-800-668-7171

Phone: 1-888-352-2249

SDS Internet Address: https://sds.sealedair.com

Emergency telephone number: 1-800-851-7145 (U.S.); 1-651-917-6133 (Int'l)

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER. CORROSIVE. CAUSES SKIN AND EYE BURNS. HARMFUL OR FATAL IF SWALLOWED.

Principal routes of exposure: Eye contact. Skin contact. Inhalation.

Eye contact: Corrosive. Causes permanent eye damage, including blindness.

Skin contact: Corrosive. Causes permanent damage.

Inhalation: May cause irritation and corrosive effects to nose, throat and respiratory tract.

Ingestion: Corrosive. Causes burns to mouth, throat and stomach.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS#	Weight %	LD50 Oral - Rat (mg/kg)	LD50 Dermal - Rabbit	LC50 Inhalation - Rat
Sodium hypochlorite	7681-52-9	1 - 5%	5000	>10000 mg/kg	Not available
Potassium hydroxide	1310-58-3	1 - 5%	273	Not available	Not available

4. FIRST AID MEASURES

Eye contact: Immediately flush eyes with running water for 15-20 minutes, keeping eyelids open. Get medical

attention immediately.

Skin contact: Immediately flush with plenty of water for 15-20 minutes. Get medical attention immediately.

Inhalation: If breathing is affected, remove to fresh air. Get medical attention immediately.

Ingestion:

If swallowed, rinse mouth. Give a cupful of water or milk. THEN IMMEDIATELY CONTACT A
PHYSICIAN OR POISON CENTER. DO NOT induce vomiting unless directed to do so by medical

personnel. Never give anything by mouth to an unconscious person.

Aggravated Medical Conditions: Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc.,

may be more susceptible to irritating effects.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: The product is not flammable. Extinguish fire using agent suitable for surrounding fire.

Specific hazards: Not applicable.

Unusual hazards: Corrosive material (See sections 8 and 10).

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH

(approved or equivalent) and full protective gear.

Extinguishing media which must not be used for safety reasons: No information available.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Use personal protective equipment.

Clean-up methods - large spillage. Prevent product from entering drains. Soak up with inert absorbent **Environmental precautions** and clean-up methods:

material. Sweep up and shovel into suitable containers for disposal. Use a water rinse for final

clean-up.

7. HANDLING AND STORAGE

Handling: Avoid contact with skin, eves and clothing. Do not taste or swallow, Avoid breathing vapors or mists. Use only with adequate ventilation. Remove and wash contaminated clothing and footwear before re-use. Wash thoroughly after handling. Mix only with water. DO NOT MIX WITH ACIDS, TOILET BOWL CLEANERS, AMMONIA, OR ANY OTHER CHEMICAL. Can react to release chlorine gas. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

Storage: Protect from freezing. Keep tightly closed in a dry, cool and well-ventilated place. KEEP OUT OF REACH OF CHILDREN.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures to reduce exposure:

Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained.

Personal Protective Equipment

Eye protection: Chemical-splash goggles. Hand protection: Chemical-resistant gloves

Skin and body protection: Protective footwear. If major exposure is possible, wear suitable protective clothing and footwear. Respiratory protection: In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program

that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever

workplace conditions warrant a respirator's use.

Handle in accordance with good industrial hygiene and safety practice. Hygiene measures:

Ingredient(s)	CAS#	ACGIH	OSHA	Mexico
Potassium hydroxide	1310-58-3	2 mg/m³ (Ceiling)		

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid Bulk density: No information available Appearance: Liquid Evaporation Rate: No information available Specific gravity: 1.097

Vapor density: No information available Boiling point/range: Not determined

Decomposition temperature: Not determined

Solubility: Completely Soluble

Solubility in other solvents: No information available Partition coefficient (n-octanol/water): No information available

Elemental Phosphorus: 0 % by wt. pH: 12.65

Explosion limits: - upper: Not determined - lower: Not determined

Color: Clear, Straw Odor: Chlorine

Melting point/range: Not determined

Autoignition temperature: No information available

Density: 9.15 lbs/gal 1.097 Kg/L Flash point: > 200 °F > 93.3 °C Viscosity: No information available

VOC: 0 %

Dilution pH: 11.36 @ 1:32

10. STABILITY AND REACTIVITY

Stability: The product is stable

Polymerization: Hazardous polymerization does not occur.

Hazardous decomposition products: None reasonably foreseeable. Materials to avoid: Acids. Ammonia. Ammonium salts.

SUMA DIP K1 Liquid Presoak

^{* -} Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

11. TOXICOLOGICAL INFORMATION

Acute toxicity: Corrosive. Oral LD50 estimated to be between 4000 - 5000 mg/kg; Dermal LD50 estimated to be >

2000 mg/kg

Component Information: See Section 3.

Chronic toxicity: None known

Specific effects

Carcinogenic effects: None known Mutagenic effects: None known Reproductive toxicity: None known Target organ effects: None known

12. ECOLOGICAL INFORMATION

Environmental Information: No data available.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products:

This product, as sold, if discarded or disposed, is a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Dispose in compliance with all Federal, state, provincial, and local laws and regulations.

RCRA Hazard Class (undiluted product): D002 Corrosive Waste

14. TRANSPORT INFORMATION

DOT/TDG/IMDG: Proper shipping descriptions can vary by pack size. Please refer to the Diversey HazMat Library, http://naextranet.diversey.com/dot/, for up to date shipping information.

<u>DOT (Ground) Bill of Lading Description:</u> UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S., (potassium hydroxide, sodium hypochlorite), 8, II

<u>IMDG (Ocean) Bill of Lading Description:</u> UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S., (potassium hydroxide, sodium hypochlorite), 8, II

15. REGULATORY INFORMATION

International Inventories at CAS# Level

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL).

U.S. Regulations

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65.

RIGHT TO KNOW (RTK)

Ingredient(s)	CAS#	MARTK:	NJRTK:	PARTK:	RIRTK:
Water	7732-18-5	-	-	-	-
Potassium polyacrylate	25608-12-2	-	-	-	-
Sodium silicate	1344-09-8	-	-	-	-
Sodium hypochlorite	7681-52-9	Х	Х	Х	Х
Potassium hydroxide	1310-58-3	X	X	X	X

CERCLA/ SARA

Ingredient(s)	CAS#	Weight %	CERCLA/SARA RQ (lbs)	Section 302 TPQ (lbs)	Section 313
Sodium hypochlorite	7681-52-9	1 - 5%	100		
Potassium hydroxide	1310-58-3	1 - 5%	1000		

SARA 311/312 Hazard Categories

Immediate:	X
Delayed:	-
Fire:	-
Reactivity:	-

Sudden Release of Pressure:

Canadian Regulations

WHMIS hazard class: E Corrosive material.



16. OTHER INFORMATION

Reason for revision:
Prepared by:
Additional advice:

Not applicable
NAPRAC

NAPRAC

This product

Additional advice:

• This product has been classified in accordance with hazard criteria of the Controlled Products

Regulations and the MSDS contains all the information required by the Controlled Products

Regulations

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.